

**ENVIRO**

# Solutions™

# 82

## BARRICADE SEALER/ FLOOR FINISH

- An acrylic blend of polymers with excellent protective properties
- Resists the penetration of over 30 common staining and soiling agents
- Excellent durability, ideal for scrub and recoat
- Recommended for spray buffing with floor machines up to 1000 RPM
- UL Approved for slip resistance

### STRIP AND RECOAT

- Before application, remove old coatings with Enviro-Solutions #85 Scrub Free Stripper or #90 Clean Cut Concentrated Stripper
- Pick up stripper solution using a mop or wet vacuum.
- Thoroughly rinse and neutralize floor

- Apply 2 to 4 coats of Enviro-Solutions #82 Barricade Sealer/Floor Finish
- Allow at least 15 minutes after dry to touch between coats

### SCRUB AND RECOAT

- Dry mop area
- Scrub with Enviro-Solutions #70 or #91, then rinse
- Apply Enviro-Solutions #82 Barricade Sealer/Floor Finish with a finish mop

### BUFFING AND BURNISHING

- Ideal for buffing with floor machines up to 1000 RPM.

### SIZES:

3.78 L (1.0 U.S. gallon)  
18.9 L (5.0 U.S. gallon)

### DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

### PERSONAL PROTECTION:

Refer to MSDS for suggestions and/or requirements.



### PACKAGING

Wherever possible, bottles and pails made from recycled plastic (10 - 25%). Can be recycled where facilities exist. Boxes made from recycled cardboard (94 - 100%).



### HEALTH & SAFETY

Product contains a low odor, safe solvent and surfactant system.

### Product does not contain:

Formaldehyde	CAS#	50-00-0
Glycol Ether DM	CAS#	111-77-3
Nonyl Phenol	CAS#	9016-45-9
Glycol Ether DE	CAS#	111-90-0
Dibutyl Phthalate	CAS#	87-74-2
Ethylene Glycol		
Monobutyl Ether	CAS#	111-76-2

Zinc or other heavy metals to disrupt the natural biodegradation process.



### TOXICITY

Acute Oral/Dermal Product considered essentially non-toxic according to WHMIS regulations.



### AQUATIC TOXICITY

Product exceeds recognized acute toxicity standards for fish, invertebrate and algae at use dilution.



### CERTIFIED

Environmental Choice Program  
CCD-147A-Hard Floor Care Products



Floor coating and finishing material classified by Underwriters Laboratories Inc. as to slip resistance only 18RL  
FTM-1



### GS-40 CERTIFIED

This product meets the Green Seal™ environmental standard for industrial and institutional floor-care products based on its reduced human and aquatic toxicity and reduced smog production potential.

**ENVIRO**  
**Solutions™**

Distributed By:

\* Reg. TM of:  
Enviro-Solutions Ltd.  
Peterborough, Ontario K9J 8N4  
Burlington, VT 05401  
toll free: 1-877-674-4373  
fax: (705) 745-7358  
www.enviro-solution.com



Enviro-Solutions ... Good Clean Products