

**ENVIRO**

**Solutions™**

**89**

## BLOCKADE

All Acrylic Water Base Concrete Sealer

### END USE APPLICATIONS

- **Thermoplastic all acrylic water based sealer for use on concrete, terrazzo and other masonry floors and walls**
- **Recommended for warehouses, food processing plants and similar facilities**
- **Food Grade Approved**
- **Not recommended for automotive garages, machine shops where brake fluid, gasoline are prevalent**

### DIRECTIONS:

See label for complete instructions.  
Temperature should be at least 50°F or 10°C when applying.  
For best results allow 8 hours before using heavy equipment on floor. To achieve maximum cure, allow 24 hours cure time

### SIZES:

18.9 L (5.0 U.S. gallon)

### BENEFITS

- Easy application – Fast drying
- Low odor
- Excellent resistance to water blushing
- Completely recovers to visually clear film when water is removed
- High level of block resistance
- Excellent stain resistance to :
  - Food Stains
  - Used Motor Oil
  - Water
  - 10% Sodium Hydroxide
  - 10% Calcium Chloride
  - 10% Sodium Chloride
- No yellowing
- UL Approved for slip resistance



#### PACKAGING

Wherever possible, bottles and pails made from recycled plastic (10 - 25%). Can be recycled where facilities exist. Boxes made from recycled cardboard (94 -100%).



#### TOXICITY

Acute Oral/Dermal Product considered essentially non-toxic according to WHMIS regulations.



#### HEALTH & SAFETY

No ingredient found on major regulatory lists.  
Non-flammable and non-corrosive at use dilution.

**ENVIRO**

**Solutions™**

Distributed By:

\* Reg. TM of:  
Enviro-Solutions Ltd.  
Peterborough, Ontario K9J 8N4  
Burlington, VT 05406  
toll free: 1-877-674-4373  
fax: (705) 745-7358  
www.enviro-solution.com

